

12 Fiber Sliding Rack Unit

ON-12FLIU 12

The Optech Network Solutions ON-FLIU Series is a rack-mount sliding Optical Fiber Interconnection Unit designed for organized termination, interconnection, cross-connection, splicing, and management of optical fiber cables.

The Optech Network Solutions ON-12FLIU is a compact 1U, 19-inch rack-mount sliding optical fiber interconnection unit designed for fiber termination, interconnection, cross-connection, splicing, and fiber management. Its sliding design provides easy access for installation, routing, splicing, and maintenance.

With a 12-fiber capacity, the ON-12FLIU supports SC, FC, LC, and ST adapter configurations and features cold-rolled steel construction with a powder-coated finish. It includes organized pigtail storage, flexible fiber routing, 20 mm cable entry, and an operating temperature range of -40°C to +60°C.

The ON-12FLIU is suitable for optical fiber networks, telecommunications, FTTx, OSP, LAN, structured cabling, fiber distribution, termination, splicing, and cross-connection applications. Model: ON-12FLIU — 12 Fiber Rack-Mount Sliding Optical Fiber Interconnection Unit, supplied unloaded; dimensions should be confirmed before publication.

Benefits

- Easy installation and dismantling
- Supports SC, FC, LC, and ST adapters
- Robust cold-rolled steel construction
- Customer specific applications
- Powder-coated surface for enhanced protection
- Ideal for telecom, LAN, FTTx, and OSP applications

Features

- Standard 19-inch rack-mount design
- Sliding construction for easy access
- Modular design for flexible fiber management
- Dedicated space for fiber splicing
- Pigtail storage with organized fiber routing
- Ample internal space for maintenance

Applications

- Optical Fiber Distribution
- Telecom Networks
- FTTx Networks
- Outside Plant (OSP) installations

Distributed By:
Optech Network Solutions
Plot Number 24, Morta,
Ghaziabad 201003
+91 9910557119
sales@optechnetwork.com

The logos and names referenced in this document are the exclusive property of their respective owners. Any unauthorized use, reproduction, or distribution of these logos or names without the express permission of the respective owners is strictly prohibited. Such unauthorized actions may result in legal consequences, including but not limited to intellectual property infringement claims.

Powered By:
Optech Network Solutions.
Plot Number 24, Morta,
Ghaziabad 201003
+91 9910557119
sales@optechnetwork.com

- Fiber Distribution
- Fiber Termination
- Fiber Splicing and Protection

Technical Specification

Product Type	Rack-Mount Sliding Optical Fiber Interconnection Unit
Fiber Capacity	12 Fiber
Mounting	19-inch Standard Rack Mount
Rack Height	1U (44.4 mm)
Dimensions	480 × 310 × 44.4 mm*
Suitable Adapter	SC / FC / LC / ST
Material	Cold Rolled Steel
Cable Entry	20 mm
Surface Finish	Powder Coating
Operating Temperature	-40°C to +60°C
Application	Fiber Termination, Splicing, Interconnection and Cross-Connection

Mechanical Construction

The ON-12FLIU is constructed using cold-rolled steel with a powder-coated finish for a robust rack-mount enclosure.

The sliding mechanism provides convenient access to the internal fiber-management area for installation, splicing, routing, and maintenance activities.

Distributed By:
Optech Network Solutions
Plot Number 24, Morta,
Ghaziabad 201003
+91 9910557119
sales@optechnetwork.com

The logos and names referenced in this document are the exclusive property of their respective owners. Any unauthorized use, reproduction, or distribution of these logos or names without the express permission of the respective owners is strictly prohibited. Such unauthorized actions may result in legal consequences, including but not limited to intellectual property infringement claims.

Powered By:
Optech Network Solutions.
Plot Number 24, Morta,
Ghaziabad 201003
+91 9910557119
sales@optechnetwork.com